

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Original) A cutting arrangement which is disposed on a distance of travel of a web of corrugated board (1) that is continuously produced by a corrugating machine, the cutting arrangement comprising
 - a. a blade shaft (32) which is mounted for drivable rotation about a blade-shaft axis of rotation (31) and which has at least one circular blade (34); and
 - b. a brush roll (16; 16a; 16d) which is disposed opposite the blade shaft (32) and mounted for rotation about a brush-roll axis of rotation (15), supporting the web of corrugated board (1), which passes between the blade shaft (32) and the brush roll (16; 16a; 16d), when the web of corrugated board (1) is cut by the at least one circular blade (34);
 - c. the brush roll (16; 16a; 16d) possessing shells (37; 37a; 37b; 37c; 37d) which are disposed on a roll core (17; 17a; 17d) and have a cross-sectional shape of a segment of a circle and which have

- i. an outside (39) and an inside (40) that is turned towards the roll core (17; 17a; 17d);
- ii. bristles which stand out from the outside (39);
- iii. torque-transmission means (44, 45, 46; 52, 54; 75) for transmitting torque from the roll core (17; 17a; 17d) to the shells (37; 37a; 37b; 37c; 37d); and
- iv. fastening means (49, 51; 75) for fixing the shells (37; 37a; 37b; 37c; 37d) to the roll core (17; 17a).

2. (Currently Amended) A cutting arrangement according to claim 1, ~~characterized in that~~ wherein the shells (37; 37a; 37b; 37c; 37d) are half-shells.

3. (Currently Amended) A cutting arrangement according to claim 1 ~~or 2, characterized in that~~ wherein the shells (37; 37a; 37b; 37c; 37d) form a closed brush sleeve (38; 38a) on the roll core (17; 17a).

4. (Currently Amended) A cutting arrangement according to ~~one of the preceding claims~~ claim 1, ~~characterized in that~~ wherein annular ribs (42; 42a; 42d) are provided on the roll core (17; 17a; 17d), which project radially at least along part of the periphery.

5. (Currently Amended) A cutting arrangement according to claim 4, ~~characterized in that~~ wherein ring grooves (43; 53; 43d) are provided on the inside (40) of the shells (37; 37a; 37b; 37c; 37d), which cooperate with the ribs (42; 42a; 42d) for fixing the shells (37; 37a; 37b; 37c; 37d) axially and/or for fixing the shells (37; 37a; 37b; 37c; 37d) tangentially.

6. (Currently Amended) A cutting arrangement according to ~~one of the preceding claims~~ claim 1, ~~characterized in that~~ wherein holes (44, 46; 69, 72) are provided in the roll core (17; 17d) and on the inside (40) of the shells (37; 37d), respectively accommodating a fastening pin (45; 75) for non-rotary connection of the shell (37; 37d) with the roll core (17; 17d).

7. (Currently Amended) A cutting arrangement according to ~~one of the preceding claims~~ claim 1, ~~characterized in that~~ wherein a first shell (37) comprises a first fastening means and a second shell (37) comprises a second fastening means for connection of the first shell (37) with the second shell (37) on the roll core (17).

8. (Currently Amended) A cutting arrangement according to ~~one of the preceding claims~~ claim 1, ~~characterized in that~~ wherein in the vicinity of the axial or tangential ends of the shells (37c; 37d), the bunches of bristles (61c, 62c, 65) incline towards the respective end, in particular combining with a radius to make an angle of $b > 0^\circ$.

9. (Currently Amended) A cutting arrangement according to ~~one of the preceding claims~~ claim 1, ~~characterized in that~~ wherein two adjacent shells (37b) interengage in the way of fingers in the vicinity of their respective tangential ends.

10. (Currently Amended) A cutting arrangement according to claim 6, ~~characterized in that~~ wherein the fastening pin (75) comprises two threaded portions (76, 77) of different pitch.

11. (Currently Amended) A shell for use in a cutting arrangement according to ~~one of the preceding claims~~ claim 1 for being fixed to a roll core (17; 17a; 17d), the shell comprising
a. a basic structure (57; 57a) in the cross-sectional shape of a segment of a circle;

- b. an outside (39) and an inside (40);
- c. bristles which project outwards from the outside (40);
- d. torque-transmission means (44, 45, 46; 52, 54; 75) for transmitting torque from the roll core (17; 17a; 17d) to the basic structure (57; 57a); and
- e. fastening means (49, 51; 75) for fixing the basic structure (57; 57a) to the roll core (17; 17a; 17d).

12. (New) A cutting arrangement according to claim 4, wherein ring grooves (43; 53; 43d) are provided on the inside (40) of the shells (37; 37a; 37b; 37c; 37d), which cooperate with the ribs (42; 42a; 42d) for fixing the shells (37; 37a; 37b; 37c; 37d) tangentially.